

**TECHNICAL DATA**

**Leddura 2Share Pro 75"**

**LET'S GET  
SPECIFIC!**

**Share, inspire, have fun!**  
**With CTOUCH by your side.**

**CTOUCH<sup>®</sup>**

## Product number

- Leddura 2Share Pro 75"

11050275

## Touch system

- Touch system: Adaptive touch
- Touch point: 32 Point
- Touch tools: Hands or other solid (soft tip) object
- Accuracy: ±2mm
- Touch Resolution: 32768 x 32768 (pixels)
- Interface: USB 2.0 compatible (full speed) HID compliant, Plug & Play compatible. Backwards compatible with USB 1.1
- Supported OS: Windows, macOS, Android and Chrome
- Touch driver: Not required for 32 touch points (under Windows); macOS needs drivers for gestures.

## Panel

- Diagonal size: 74,52" (1893 mm)
- Panel technology: TFT LCD
- Panel resolution: 3840 x 2160
- Frame rate: 60 Hz
- Brightness: 350 cd/m<sup>2</sup>
- Aspect Ratio: 16:9
- Contrast Ratio (Static): 1200:1
- Contrast Ratio (Dynamic): 5000:1
- Response time: 8 ms
- Display Colours: 1.07 Billion (10 bits)
- Pixel pitch (W x H): 0.429 x 0.429 mm
- Viewing Angle: 178° / 178°
- Backlight type: Direct LED
- Service Life: > 30.000 Hours
- Installation: Landscape

## Connectivity

- Video input (digital): 3x HDMI 2.0, 1x DP 1.2
- Video input (analog): 1x VGA
- Audio input: 1x Mini Jack
- Audio output: 1x S/PDIF Optical, 1x Mini Jack
- USB: 4x USB 2.0
- Touch: 2x USB-B
- RS232C: 1x DB-9
- LAN port: 1x RJ45 10/100/1000 BaseT
- Connection Bay
- OPS slot: 1x

## Video

- PSM: Warm / Cool / Normal
- Picture Mode: Dynamic / Standard / Soft / User
- Freeze function: Yes
- Backlight mute function: Yes
- Blue Light Filter

## Sound: designed, tuned, built by HARMAN

- Transducers: 2 Stereo JBL® 3-Way Speakers (tweeter, mid-range and woofer)
- Amplifier power: 80 watts
- Frequency range: 60Hz - 20kHz
- JBL® LiveStage (Virtual) surround sound
- JBL® far-field microphones

## Meeting office application

- Advanced whiteboard & easy wireless sharing solution with:
  - Multicolour sticky notes
  - Embedded text recognition
  - Embedded room booking based on Microsoft Exchange
  - Embedded web browser
  - Barco ClickShare full integration option
- Runs on dedicated Windows 10 OPS

## Features / Convenience

- Gesture recognition: Yes, refer to the CTOUCH manual
- HDCP compliance 2.2
- Thickness of safety glass: 4 mm (hardness Mohs 7)
- Network controllable input: via RS232C & LAN
- Human presence detection
- BRIX compatible: based on a futureproof modular platform

## OSD

- Language: Dutch, English, French, German, Spanish

## Power

- Power Supply: AC 100-240 V 50 / 60Hz
- Power Consumption (in Operation): 150W
- Power Consumption (in Standby): <= 0.5 W
- Ambient light sensor: Yes

## Quality approvals

- Regulatory approvals: CE, FCC
- Green approval: Energy Star, RoHS complaint, WEEE
- ISO Standard: ISO9001 and ISO14001

## Dimensions & Weight

- Product dimensions (WxHxD): 1745 x 1036 x 113 (mm)
- Product weight: 70 kg
- Vesa Mount (WxH): 600 x 400 (mm), M8 screw

## Product accessories

- Accessories pack: power cable, USB cable, HDMI cable, remote control, 2 passive pens, Quick Start Guide & Warranty card

## Logistics information

- Box size (WxHxD): 1866 x 1170 x 231 (mm)
- Gross weight: 79 kg
- EAN no.:

8719481480554

## Check out the Leddura 2Share folder for more information.

All rights reserved. CTOUCH products and services mentioned herein as well as their respective logos are trademarks or registered trademarks of CTOUCH Europe B.V.. All other product and service names mentioned are the trademarks of their respective owners. All weights and dimensions are approximate. Product specifications are subject to change without prior notification.