

ViewSonic® PROJECTOR **LS810**

Key Features

- Laser phosphor technology
- 20,000 hours lifespan
- 0.24 ultra-short throw ratio
- Wide colour gamut coverage
- Ultra-high contrast ratio 100,000:1



Product Description

Powered by a Laser Phosphor light source system, the ViewSonic LS810 laser projector provides resource efficient solution when compared to traditional lamp-based projectors. Pure laser lasting up to 20,000 hours which delivers long-term, virtually maintenance-free usage. Featuring 1280x800 WXGA resolution and 5,200 ANSI Lumens of brightness, the ViewSonic LS810 Laser Projector is the ideal solution for high-end retail and luxury commercial use. With a 0.24 ultra-short throw ratio, the LS810 can be placed just inches away from a wall or screen to project a huge image. High contrast ratio and pure laser light source displays superior image quality than other DLP projectors.

Visit Us - www.viewsonic.com

DISPLAY

Type:	TI DMD 0.65
Resolution:	1280x800 (WXGA)
F Stop / Focal Length mm:	2.4
Focus / Zoom:	Adjustable by OSD menu / N/A
Keystone:	+/- 30° (Horizontal / Vertical)
Auto keystone:	Yes (Vertical)
Display Size:	80" ~ 150"
Throw Distance:	0.43 m ~ 0.8 m
Throw Ratio:	0.241
Lamp Power:	390 W
Lamp Life (Normal / SuperEco Mode):	15,000 / 20,000 (Ecco mode) (hours)
Brightness:	5,200 ANSI Lumens
Contrast Ratio:	100,000:1
Color Depth:	1.07 Billion Colors (30 bits per color)
Color Wheel:	Dual Wheel System (RYGW) / 7200rpm
Optical Offset:	137.6 +-5%

AUDIO

Speaker:	8W Cube x2
----------	------------

INPUT SIGNAL

Video:	480i and 576i, 480p and 576p, 720p, 1080i, 1080p
Frequency (H/V):	15 ~ 100 KHz / 24 ~ 120 Hz

COMPATABILITY

PC:	Support up to 1920x1080@60Hz
Mac:	Support up to 1920x1080@60Hz

CONNECTOR

VGA Input:	x2
VGA Output:	x1
Digital Input:	HDMI x1 / HDMI (MHL2.0) x1
Composite Input:	RCA x1
S-Video Input:	x1
Component:	x2 (Share with VGA input)
Audio Input:	3.5mm mini jack x1, RCA(L/R) x1
Audio Output:	3.5mm mini jack x1, RCA(L/R) x1
Control:	RS-232
USB:	Type A x1 (Power Charging) / Mini type B x1 (Maintenance and mouse control) / Micro USB Wire x1 (Power Charging)
Lan:	x1
3D VESA:	x1
DC Output:	x1

POWER

Voltage:	100~240Vac 50/60Hz (Auto Switching)
Power Consumption:	450 W (Max.)
Standby:	<0.5W

OPERATING CONDITION

Temperature:	0°C ~ 40°C (32°F ~ 104°F)
Humidity:	0% ~ 90% (non-condensing)

NOISE LEVEL

Normal / Eco Mode:	28dB (Eco Mode)
--------------------	-----------------

DIMENSIONS

Physical (WxDxH):	508 x 392 x165 mm/ 20" x 15.43 " x 6.5"
-------------------	---

WEIGHT

Net:	13.6 kgs / 29.96 lbs
------	----------------------

REGULATIONS

CB, cTUVus, FCC, CE, EMC, CCC, GS

PACKAGE CONTENTS

Power Cord, 1.8m, black 1 /VGA Cable, 1.8m, black x 1 / Remote Control with Batteries (With Laser pointer) x1 / Quick Start Guide (one sheet version) x1 / ViewSonic CD Wizard (With User Manual) x 1 /HDMI Cable
