Broadcast Quality Made Affordable

EPTZ NDI® | HX ZCAM



Model Number:PTEPTZ-NDI-ZCAM-G2 (white) http://ptzoptics.com/ndi/

PTZOPTICS

Broadcast & NDI® | HX Camera

The PTZOptics EPTZ-NDI ZCAM is a 1080p @ 30fps camera with a 4K image sensor for capturing HD images at short distances. With support for 3G-SDI and IP streaming, this camera is ideal for delivering high definition video signals to broadcast or live streaming applications.

KEY FEATURES

- Panasonic 1/2.5" HD CMOS Sensor
- Full 1920x1080p HD Resolution up to 30 FPS
- 104° Horizontal Field of View
- 2D & 3D noise reduction
- Simultaneous Dual 3G-SDI, NDI® | HX / High Definition IP Outputs
- Dual SDI output (Full view / EPTZ view)
- NDI® JHX, H.264, H.265, & MJPEG IP streaming outputs
- RTMP / RTMPS, RTSP, and NDI® | HX
- AAC Audio encoding over NDI® | HX / RTSP / RTMP / RTMPS
- Dynamic / Static IP addressing (Hold D-Pad left for 5+ sec to toggle)
- High performance in low light scenarios
- RS-485, VISCA over IP, & NDI available for camera control
- Four (4) Std 1/4-20 female threads for camera mounting
- PoE 802.3af (Power over Ethernet) or 12VDC
- 3-year warranty

WHAT'S IN THE BOX

EPTZ NDI® | HX ZCAM Camera Power Adapter User Manual



Camera & Lens	
Video Sensor	1/2.5" CMOS, 8.51 Mega Pixels
Frame Rates	1080p-30/25, 1080i-30/25, 720p-30/25
Focal Length	F=2.8mm
Digital Zoom	Up to 8x
Field of View	104°
Min Lux	0.5 Lux at F1.8, AGC ON
Shutter Speed	1/30s - 1/10000s
SNR	≥55dB
Vertical Flip & Mirror	Supported
Horizontal Field of View	42° (tele) to 104° (wide)
Vertical Field of View	24° (tele) to 65°(wide)
Working Environment	Indoor

Full camera view
EPTZ video feed
3G-SDI, NDI® HX
RS485 VISCA, Pelco-D, Pelco-P
2400/4800/9600 bits
JEITA type Power Adapter (DC in 12V)

2.8W x 2.4H x 5.6D (6.3 w/ SDI)
72W x 60H x 143mm (162 w/ SDI)
1.4 lbs 0.63 kg
9.4W x 4.7D x 4.3H
240W x 120D x 110H
2.0 lbs 0.90 kg