



Pixel calibration for perfect colour and brightness



4 corner protector design



Compatibility



Easy operation



Special lock design



Modularity – easy to disassemble and install

MODEL NAME	LR-I29D	LR-I39D
Application	Indoor	Indoor
Pixel Pitch (in mm)	2.9	3.9
LED Type	SMD	SMD
LED Lifetime (In Hours)	50,000	50,000
Brightness (cd/m ²)	1000	1000
Contrast Ratio	4000:1	4000:1
Frame Rate (Hz/sec)	60	60
Refresh Rate (Hz/sec)	3840	3840
Cabinet Dimension WxHxD (in mm)	500x500x73	500x500x73
Module Dimension (in MM)	250x250	250x250
Physical Resolution	168x168	128x128
weight (Kg/Cabinet)	8	8
Service Access	Front	Front
Optimal Viewing Angle (HM)	160° /120°	160° /120°
Storage Temperature	-10°C~60°C	-10°C~60°C
Working Temperature	-20°C~50°C	-20°C~50°C
Relative Humidity	≤95%	≤95%
Storage Humidity	≤45%	≤45%
Voltage	220-240v	220-240v
Power Consumption (Avg) (in W/m ²)	140	140
Power Consumption (Max) (in W/m ²)	460	460
Heat generation-Max (BTU/m ²)	1569.6	1569.6
MTBF (in hours)	10,000	10,000
Protection Level	IP20	IP20
Colour (M)	65536	65536
Grey Scale	16	16
Certification	BIS	BIS
Physical density	1,12,896 pixels/m ²	65,536 pixels/m ²