

Light-weight screen



High transparency



High brightness




Multiple pixel pitch and spacing option



Unique and reliable lock



Power indicator lamp



Ultra-thin design for seamless blend

MODEL NAME	LT-IO39D	LT-IO78D
Application	Indoor	Indoor
Pixel Pitch (in mm)	3.9 x 78	78 x 10.4
LED Type	SMD	SMD
LED Lifetime (In Hours)	1,00,000	1,00,000
Brightness (cd/m <sup>2</sup> )	4000	5000
Contrast Ratio	4000:1	4000:1
Frame Rate (Hz/sec)	60	60
Refresh Rate (Hz/sec)	1920	1920
Cabinet Dimension W x H x D (in mm)	1000X500X78.5	500X500X67
Module Dimension (in MM)	500X250	500X166.7
Physical Resolution	256X64	64x48
weight (Kg/Cabinet)	10.2	5.8
Service Access	Rear	Rear
Optimal Viewing Angle (H/M)	120° /120°	100° /100°
Storage Temperature	-10°C~90°C	-10°C~90°C
Working Temperature	-10°C~45°C	-10°C~45°C
Relative Humidity	≤95%	≤95%
Storage Humidity	≤45%	≤45%
Voltage	100-240v	100-240v
Power Consumption (Avg) (in W/m <sup>2</sup> )	214	200
Power Consumption (Max) (in W/m <sup>2</sup> )	624	500
Heat generation-Max (BTU/m <sup>2</sup> )	2129.1	1706
MTBF (in hours)	10,000	10,000
Protection Level	IP2X/IP2X	IP2X/IP2X
Colour (M)	65536	65536
Grey Scale	16	16
Certification	BIS	BIS
Physical density	32,768 pixels/m <sup>2</sup>	12,288 pixels/m <sup>2</sup>