



Poly ATA 402 2FXS Voice Port VoIP Adapter with Open SIP and Power Supply (8F3H5AA)



Overview

Make any phone an IP phone

Convert analog phones to digital IP phones – easily and benefit from the sustainable and cost-effective solution that allows you to retain existing phones, streamline management and faxing. No ethernet, Wi-Fi [1] enables VoIP access without ethernet.

Extend analog phone capability

Reutilize your analog phone with the Poly ATA 400 Series and take advantage of VoIP calling. Get the advantage of digitization, access a dial tone over the network without replacing your existing phones.

Management via PDMS-SP & APIs

The PDMS-SP cloud service lets you configure, modify, troubleshoot, and maintain all the Poly ATA 400 devices and phones they are connected to across your organization. API support enables real-time ATA status monitoring.

Features

Two FXS ports for VoIP & fax

Two FXS ports let you make and receive calls and faxes over the internet using SIP-based VoIP and T.38 services. Multiple Poly ATA 402 devices can be used in a single room. A PC port provides a bridge to other network devices.

Easy deployment

Effortless deployment with Poly ATA 402: connect analog phone, power source, and internet for a seamless transition to digital IP communication. Repurpose phones in minutes with a simple setup.

Analog to digital made easy

Poly ATA 402 helps analog telephony join the digital world, transitioning from Public Switched Telephone Network (PSTN). As regions worldwide shift to digital networks, our solution keeps you connected.

Wi-Fi via USB

With a WiFi USB adapter, sold separately, you can access Wi-Fi for VoIP even when ethernet isn't available, keeping your communication flowing smoothly in any situation.

Communication platforms

The Poly ATA 402 works with your existing infrastructure. The Poly ATA is Zoom certified and Microsoft supported through Microsoft Teams SIP Gateway.^[2]

Legendary Poly audio quality

Bring clearer communication to your analog phones with high-quality sound built on Poly's decades of audio expertise.

[1] WiFi connectivity requires a Wi-Fi USB adapter, sold separately.

[2] The Poly ATA 402 is Microsoft supported. Through Microsoft Teams SIP Gateway, it provides basic telephony on Microsoft Teams.

Additional specifications

Audio codecs	OPUS; G.711 (A-law, 64 kbps)
Certifications and compliances	FCC part 15 (CFR 47) class B, CE
Certified collaboration software	Zoom ^[1]
Color	Black
Country of origin	Made in China
Datasheet photo 1	https://ssl-product-images.www8-hp.com/digmedialib/prodimg/lowres/c08757215.png
Datasheet photo 2	https://ssl-product-images.www8-hp.com/digmedialib/prodimg/lowres/c08757245.png
Management Software	Polycom Device Management Service for Service Providers (PDMS-SP) Cloud Management
Manufacturer Warranty	Poly standard one-year limited warranty
Minimum dimensions (W x D x H)	9.6 x 9.6 x 2.2 cm
Network protocols, supported	LLDP-MED for VLAN discovery; IPv4; TCP (RFC 793) in SSL/TLS; Domain Name System (DNS): A records (RFC 1706), SRV records (RFC 2782), RTP (RFC 1889, 1890), RFC 5966
Operating humidity range	5 to 95%
Operating temperature range	0 to 40°C
Package dimensions (W x D x H)	11.9 x 20.2 x 5.2 cm
Package weight	112.1 g
Ports	1 RJ-45; 1 USB 2.0 Type-A (for media and storage applications); 2 RJ-11
Power	External universal AC adapter: 5V 1A DC; 100 - 240 VAC, 0.3 A, 50/60 Hz (26–34 VA)
Security management	HTTPS secure provisioning; Local Access Interface: IVR password
Storage temperature range	-40 to 70°C
Telephony and call handling features	Call return; Call routing rules
UNSPSC code	43201552
UPC number	197497475784
VoIP features	SIPv2 (RFC 3261, 3262, 3263, 3264); Four (4) service provider configuration profile assignments (ITSP 1–4)
Weight	85 g
What's in the box	Quick start guide; AC power adapter; Ethernet cable; ATA400 Voice Service Bridge and Telephone Adapter

[1] Additional service provider platforms are supported.

Disclaimer — Copyright

© Copyright 2024 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Generated by Dynamic Collateral Tool – (sg-en) – Jan 17, 2024 12:38 PM UTC+0000