

LS5WT WALL SPEAKERS

Designed to provide high-quality audio in small and large meeting spaces.



- > Speaker Type: 2-way, wall-mount speaker
 - > Frequency Range: Offers a frequency response of 80 Hz – 19 kHz, ensuring a broad audio spectrum for high-quality sound.
 - > Power Handling: Capable of handling 30 watts RMS and 80 watts peak.
 - > Sensitivity: Delivers 90 dB SPL at 1 watt, measured from 1 meter.
 - > Connectivity: Supports both 8 ohm nominal impedance and 70/100V taps for efficient power distribution and simplified wiring.
 - > Coverage Angle: 110° conical coverage for wide sound distribution
 - > Woofer: 6.5 inch polypropylene cone with moisture-resistant rubber coating.
 - > Tweeter: 0.5 inch Mylar tweeter for clear high-frequency sound reproduction
 - > Dimensions: 11.26 in. × 8.27 in. × 7.48 in. (286 mm(H) × 210 mm(W) × 190 mm(D)). 5 lbs (2.27 kg) per speaker, designed for easy wall mounting with an included adjustable bracket.
-

LS5WT WALL SPEAKERS

Specifications

Part Number	• 910-151-002-01
Speaker Type	• 2-way, Wall Mount Speaker
Frequency Range	• 80 Hz - 19 kHz
Power Handling	• 30 watts RMS, 80 watts Peak
Nominal Sensitivity	• 90 dB SPL, 1 W @ 1 m
Nominal Coverage Angle	• 110° Conical Coverage
Nominal Impedance	• 80 ohms
Transformer Taps	• 70 V – 30 W, 15 W, 7.5 W, 3.8 W, 1.9 W • 100V – Null, 30 W, 15 W, 7.5 W, 3.8 W Woofer diameter: 6.5 in. (165 mm)
Woofer	• 5 in. (127 mm) poly-propylene cone with moisture resistant rubber coating
Tweeter	• 0.5 in. (12.7 mm) Mylar Tweeter
Termination	• Two (2) Input Termination Screws (Red = Positive Post, Silver = Negative Post)
Dimensions	• 11.26 in. x 8.27 in. x 7.48 in. (286 mm(H) x 210 mm(W) x 190 mm(D))
Net Weight (each)	• 5 lbs (2.27 Kg)



Scan this Code,
to learn more

SALES AND INQUIRIES

Headquarters

5225 Wiley Post Way
Suite 500
Salt Lake City, UT 84116

US & Canada

Tel: +1.801.975.7200

International

Tel: +1.801.975.7200

Sales

Tel: +1.801.975.7200
sales@clearone.com

Tech Support

Tel: +1.801.974.3760
audiotechsupport@clearone.com